DUAL WALL FABRICATED 22.5º BENDS
4" - 30" DIAMETER

PIPE SIZE	A	JOINT
4 in (100 mm)	4.5 in (114 mm)	*
6 in (150 mm)	5.4 in (137 mm)	*
8 in (200 mm)	7.6 in (194 mm)	*
10 in (250 mm)	7.8 in (197 mm)	*
12 in (300 mm)	9.6 in (244 mm)	*
12 in (300 mm)	5.8 in (146 mm)	ST
12 in (300 mm)	5.8 in (146 mm)	WT
15 in (375 mm)	13.1 in (334 mm)	*
15 in (375 mm)	5.4 in (137 mm)	ST
15 in (375 mm)	5.4 in (137 mm)	WT
18 in (450 mm)	14.3 in (363 mm)	*
18 in (450 mm)	6.9 in (174 mm)	ST
18 in (450 mm)	6.9 in (174 mm)	WT
24 in (600 mm)	18.9 in (480 mm)	*
24 in (600 mm)	9.5 in (240 mm)	ST
24 in (600 mm)	9.5 in (240 mm)	WT



PLAIN END



ST & WT (INCLUDES 2 GASKETS)

* = PLAIN END
ST = SOIL TIGHT
WT = WATER TIGHT

NOTE ALL FITTINGS DIMENSIONS ARE FOR REFERENCE ONLY

www.parsethylene-kish.com

Office Address
No.18, Mina Blvd., Africa St, Tehran/Iran
Tel: (+98 - 21) 88 20 20 60 (50 Lines) Fax: (+98 - 21) 88 20 20 81
info@parsethylene-kish.com
www.parsethylene-kish.com

DUAL WALL FABRICATED 22.5º BENDS
30" - 60" DIAMETER

PIPE SIZE	A	JOINT
30 in (750 mm)	17.9 in (455 mm)	*
30 in (750 mm)	9.7 in (245 mm)	ST
30 in (750 mm)	9.7 in (245 mm)	WT
36 in (900 mm)	21.5 in (546 mm)	*
36 in (900 mm)	11.2 in (285 mm)	ST
36 in (900 mm)	11.2 in (285 mm)	WT
42 in (1050 mm)	24.9 in (632 mm)	*
42 in (1050 mm)	14.5 in (369 mm)	ST
42 in (1050 mm)	14.5 in (369 mm)	WT
48 in (1200 mm)	23.8 in (605 mm)	*
48 in (1200 mm)	13.9 in (353 mm)	ST
48 in (1200 mm)	13.9 in (353 mm)	WT
60 in (1500 mm)	33.2 in (844 mm)	*
60 in (1500 mm)	15.2 in (387 mm)	ST
60 in (1500 mm)	15.2 in (387 mm)	WT



PLAIN END



ST & WT (INCLUDES 2 GASKETS)

* = PLAIN END
ST = SOIL TIGHT
WT = WATER TIGHT

NOTE: ALL FITTINGS DIMENSIONS ARE FOR REFERENCE ONLY

www.parsethylene-kish.com

Office Address

No.18, Mina Blvd., Africa St, Tehran/Iran
Tel: (+98 - 21) 88 20 20 60 (50 Lines) Fax: (+98 - 21) 88 20 20 81

info@parsethylene-kish.com
www.parsethylene-kish.com